

# > 2600 ATLANTIQUE LED

DESIGNED FOR LIGHTING OF GARDENS & FAÇADES



**THE 2600 ATLANTIQUE LED SERIES IS USED FOR THE LIGHTING OF GARDENS AND FAÇADES UP TO 18M HIGH.**

The top locking ring is available in AISI 316 stainless steel and increases resistance to mechanical stress and atmospheric agents. It is recommended for heavy-duty applications, such as in areas where they are driven over or near the sea. As they only require a 162 mm recess, they can also be used when a shallow depth is available.

- Cast aluminium body, phosphochromate treated and powder-painted
- Cast aluminium or AISI 316 stainless steel locking ring
- A4 stainless steel screws
- Aluminium sleeve (to be ordered separately)
- 12 mm clear flat tempered glass cover
- 22 LUMILED leds 1.2W each
- Installation in sleeve set in concrete, with a 20-30 cm gravel drain bed
- Fittings come with one 3x 1.5 mm<sup>2</sup> Ho7RNF cable, 3.0 m in length and DMX cable 3.0 m in length (only for 80 20 100)
- Class III fittings without built-in transformers are available on request
- Operated by special switchboards or directly by radio control
- Protection rating: IP 68 FULL-DRY
- Roll-over weight: 4500 Kg
- Breaking strength: IK 10 (58 Joules)



# LAMPS

## 80 20 100 LED

With 22 RGB LEDs 1.2W each  
+5° tilting LEDs  
Glass Temperature 38°C  
Weight 7.5 kg CE Class I

## 80 20 101 LED

With 22 white LEDs 1.2W each  
+5° tilting LEDs  
Glass Temperature 38°C  
Weight 7.5 kg CE Class I

## 80 20 102 LED

With 22 red LEDs 1.2W each  
+5° tilting LEDs  
Glass Temperature 38°C  
Weight 7.5 kg CE Class I

## 80 20 103


With 22 green LEDs 1.2W each  
+5° tilting LEDs  
Glass Temperature 38°C  
Weight 7.5 kg CE Class I

## 80 20 104


With 22 yellow LEDs 1.2W each  
+5° tilting LEDs  
Glass Temperature 38°C  
Weight 7.5 kg CE Class I

## 80 20 105

With 22 blue LEDs 1.2W each  
+5° tilting LEDs  
Glass Temperature 38°C  
Weight 7.5 kg CE Class I



- 80 20 100
- 80 20 101
- 80 20 102
- 80 20 103
- 80 20 104
- 80 20 105



Sleeve  
89 36 000

# ACCESSORIES



89 18 450  
2x 23° Prismatic  
Glass



89 18 455  
2x 14° Prismatic  
Glass



89 18 300  
Convex Clear  
Glass



89 22 000  
Anti-vandalism  
Protected Grid  
"GPA"



89 17 003  
IP 68 Junction Box  
with Gel  
89 17 000  
IP 67 Quick  
Connector



89 49 004  
8 x Anti-  
vandalism  
Screws + 1 Tool



89 56 050  
PC Control Software  
+ Decoder IP65



89 56 051  
Radio Control



89 56 052  
Remote Control  
IP65



89 36 000  
Sleeve



89 20 000  
AISI 316  
Round Stainless  
Steel Ring



KENDELIER LIGHTING LIMITED  
25 AINTREE AVE  
AIRPORT OAKS  
AUCKLAND  
NEW ZEALAND

TEL +64 9 915 1083  
FAX +64 9 915 1087

SALES@KENDELIER.CO.NZ  
WWW.KENDELIER.CO.NZ

NZ FREE 0800 536 335  
AUSTRALIA FREE 1800 553 817