

> 3600 SUOLO DOUBLE GLASS

DESIGNED FOR AMENITY AND AREA LIGHTING



THE 3600 SUOLO DOUBLE GLASS SERIES IS A RANGE OF GROUND RECESSED FITTINGS FOR ILLUMINATING FAÇADES UP TO 35M HIGH, USING DISCHARGE LAMPS UP TO 250W.

The double-glass system reduces the temperature of the outer glass up to 60%, enabling these fixtures to be installed in areas accessible to pedestrians, in compliance with EN 60598-2-13.

- Cast aluminium body, phosphochromate treated and powder-painted
- Cast aluminium locking ring
- Anti-vandalism A4 stainless steel screws
- PVC sleeve with aluminium locking ring
- 12 mm clear flat tempered glass cover
- Installation in sleeve set in concrete, with a 20-30 cm gravel drain bed
- Fittings come with one 3x 1.5 mm² Ho7RNF cable, 3.0m in length
- Versions for other types of lamps are available on request
- Protection rating: IP 68 FULL-DRY
- Roll-over weight: 7000 Kg
- Breaking strength: IK 10 (58 Joules)




LAMPS

80 16 114

For HQI-TS/SHP-TS 150W Lamp
+15° Tilting Lamp
Glass Temperature 69°C
Weight 20.5 kg



CE Class 1



80 16 039

For HQI-G12 150W Lamp
+15° Tilting Lamp
Glass Temperature 70°C
Weight 20.5 kg


CE Class 1



80 16 116

For HQI-TS/SHP-TS 150W Lamp
+15° Tilting Lamp
Glass Temperature 68°C
Weight 20.5 kg



CE Class 1



80 16 048

For SHP-T 100W Lamp
+15° Tilting Lamp
Glass Temperature 70°C
Weight 20.4 kg


CE Class 1



80 16 155

For HQI-TS 250W Lamp
+15° Tilting Lamp
Glass Temperature 75°C
Weight 30 kg



CE Class 1



80 16 050

For SHP-T 100W Lamp
+15° Tilting Lamp
Glass Temperature 70°C
Weight 20.4 kg


CE Class 1



80 16 035


For HQI-G12 150W Lamp
+15° Tilting Lamp
Glass Temperature 70°C
Weight 20.5 kg

CE Class 1




80 16 114
80 16 116
80 16 035
80 16 039
80 16 048
80 16 050

Sleeve included



80 16 155
Sleeve included



ACCESSORIES



89 18 300
Convex Clear Glass



89 02 000
Internal Side Louver "DIL"



89 18 100
Prismatic Glass "Activa 10°"



89 19 000
Anti-glare Louver



89 17 003
IP 68 Junction Box with Gel
89 17 000
IP 67 Quick Connector



89 18 400
Lens "Concentra"



89 04 000
Anti-vandalism Protection Grid "GPA"



89 18 201
Flat BLUE Dichroic Glass



89 18 202
Flat RED Dichroic Glass



89 18 204
Flat GREEN Dichroic Glass



89 18 203
Flat YELLOW Dichroic Glass



89 18 205
Flat Etched Dichroic Glass



KENDELIER LIGHTING LIMITED
25 AINTREE AVE
AIRPORT OAKS
AUCKLAND
NEW ZEALAND

TEL +64 9 915 1083
FAX +64 9 915 1087

SALES@KENDELIER.CO.NZ
WWW.KENDELIER.CO.NZ

NZ FREE 0800 536 335
AUSTRALIA FREE 1800 553 817