

> 3600 SUOLO

DESIGNED FOR AMENITY AND AREA LIGHTING



THE 3600 SUOLO SERIES IS A RANGE OF GROUND RECESSED FITTINGS FOR ILLUMINATING FAÇADES UP TO 35M HIGH, USING DISCHARGE LAMPS UP TO 250W.

Optics with different beam angles and asymmetrical reflectors give blades of light or uniform lighting as required.

- Cast aluminium body, phosphochromate treated and powder-painted
- Cast aluminium locking ring
- Anti-vandalism A4 stainless steel screws
- PVC sleeve with aluminium fixing ring
- 12 mm clear flat tempered glass cover
- Installation in sleeve set in concrete, with a 20-30 cm gravel drain bed
- Fittings come with one 3x 1.5 mm² Ho7RNF cable, 3.0m in length
- Versions for other types of lamps are available on request
- Protection rating IP 68 FULL-DRY
- Roll-over weight 7000 Kg
- Breaking strength IK 10 (58 Joules)





LAMPS

80 05 114

For HQI-TS/SHP-TS 150W Lamp
Fixed Lamp
Glass Temperature 176°C
Weight 17.2 kg


CE Class 1



80 05 043

For HQI-G12 150W Lamp
Fixed Lamp - Asym. Optic (θ 32°)
Glass Temperature 132°C
Weight 17.1 kg



CE Class 1



80 05 116

For HQI-TS/SHP-TS 150W Lamp
Fixed Lamp
Glass Temperature 171°C
Weight 17.2 kg



CE Class 1



80 05 048

For SHP-T 100W Lamp
Fixed Lamp
Glass Temperature 165°C
Weight 17 kg



CE Class 1



80 05 155

For HQI-TS 250W Lamp
Fixed Lamp
Glass Temperature 195°C
Weight 26 kg



CE Class 1



80 05 050

For SHP-T 100W Lamp
Fixed Lamp
Glass Temperature 162°C
Weight 17 kg



CE Class 1



80 05 042


For HQI-G12 70W Lamp
Fixed Lamp - Asym. Optic (θ 32°)
Glass Temperature 111°C
Weight 16.8 kg

CE Class 1




80 05 114
80 05 116
80 05 042
80 05 043
80 05 048
80 05 050

Sleeve Included



80 05 155
Sleeve Included



ACCESSORIES



89 18 100
Prismatic Glass
Activa 100



89 18 400
Lens Concentra



89 18 300
Convex Clear Glass



89 18 201
Flat BLUE Dichroic
Glass



89 18 202
Flat RED Dichroic
Glass



89 18 203
Flat YELLOW
Dichroic Glass



89 18 204
Flat GREEN
Dichroic Glass



89 18 205
Flat ETCHED
Glass



89 02 000
Internal Side
Louver "DIL"



89 19 000
Anti-glare Louver



89 04 000
Anti-vandalism
Protected Grid
"GPA"



KENDELIER LIGHTING LIMITED
25 AINTREE AVE
AIRPORT OAKS
AUCKLAND
NEW ZEALAND

TEL +64 9 915 1083
FAX +64 9 915 1087

SALES@KENDELIER.CO.NZ
WWW.KENDELIER.CO.NZ

NZ FREE 0800 536 335
AUSTRALIA FREE 1800 553 817